

qonvolv

KA009A
Auto Elastic Band Joining Machine





Finished Product



Finished Product

Applicable to both overlapping seam and flat splicing joining process. Outstanding consistency and productivity with output up to 12 to 15 pieces per minute.

- Flexible switching between overlapping and flat splicing process.
- Equipped with image recognition system for precise logo matching.
- Integrated with multiple stacking device.
- Automatic removal of defective products.

APPLICATIONS

Styles

Underwear or other clothing with elastic bands.

Size and Dimensions

Minimum Elastic Band Circumference:
270 mm
Collar Length: 15-65 mm

SPECIFICATIONS



Sewing Machine Head
**Brother
BAS 311HN-035**



Dimensions (mm)
L: 1,200 x W: 1,155 x H: 1,820



Stitch Type
Lockstitch (#301)



Power (W)
2,500



Compressed Air Requirement (Mpa)
0.5-0,6



Power Supply (V)
AC 220 (50Hz)



Needle
DBx1, #10 ~ #12



Max. Sewing Speed (rpm)
2,000-2,300



Changeover Time (m)
5-10



Weight (kg)
350



Output (pcs/ hr)
700-800

qonvolv

Quaternion Hong Kong Limited
13/F, Harbour Center, 25 Harbour Road
Wanchai, Hong Kong

| +852 2811 8077
| cs@qonvolv.com
| www.qonvolv.com

REL 20220706